Western Power's Asset Management System

Distribution Substation Plant Manual Chapter 7 – Superseded Equipment



Original Issue: September 2019

Content Owner/Custodian: Distribution Design and Standards

This Revision: 2 – April 2025

Date for Next Review: April 2028

© Western Power ABN 18540492861



Document control

Endorsement approvals

	Name	Title	Signature & Date
Author	Samuel Liau	Senior Distribution Standards Engineer	Signature on file
Checked by	Chris Omodei	Principal Engineer	Signature on file
Endorsed by	Ken Tiong	Engineering Team Leader	Signature on file
Approved by	Pep Ngwenya	Distribution Design & Standards Manager	Signature on file

Record of revisions

Revision No. Date EDM ver		EDM version	Revised by	Description
0	September 2019	0	Gareth Chadwick	Original (MKI MPS)
1	November 2019	2	Gareth Chadwick	Type1, 2 & 3 LV Switchgear assemblies added.
Revision No.	Date	Volt version	Revised by	Description
2	April 2025	1.0	Samuel Liau	3 yearly periodic review

Key documents providing direction and influencing this document

Doc#	Title of document						
DM# 40304923	Asset Management System						
DM# 41965928	Safety in Design Guidelines						
EDM# 50473207	DSPM Governance & Supporting Technical Documents Register						

This document gives direction to and influences the following documents

Doc#	Title of document
Various DQM documents	Distribution Substation Design Projects



Stakeholders (people that were consulted when document was updated)

Position / Function / Section

Asset Management - Asset Performance

Asset Management - Safety Environment Quality and Training

Asset Management - Grid Transformation

Asset Operations – Network Operations

Asset Operations – Operational Services

Asset Operations – Network Connection Services and Emergency Management

Business and Customer Service - Customer Service

Notification list (people to be notified when document is updated)

Position / Function / Section

Asset Management - Asset Performance

Asset Management - Safety Environment Quality and Training

Asset Management - Grid Transformation

Asset Operations – Network Operations

Asset Operations – Operational Services

Asset Operations - Network Connection Services and Emergency Management

Business and Customer Service - Customer Service


This document must not be made available to personnel outside Western Power without the prior written approval of Western Power.



Document classification and hierarchy

A key requirement of the Western Power Asset Management Policy (AMP) is to develop and maintain an Asset Management System (AMS). This Distribution Substation Plant Manual is defined as an overarching / technical / governance document within the AMS document classification and structure and sits within the planning and Program Delivery component/s of the AMS.

The AMS and the interrelationships between the collection of documents, tools and systems that are used for asset management are described in the AMS document EDM# 40304923.





Contents

1.	Intro	duction	6					
		nimer						
3.	Comp	liance with this Chapter of the Manual	6					
4.	. Scope							
5.	Super	seded Equipment Drawings	8					
	5.1	Drawing Legend	8					
	5.2	Tyree MKI Modular Package Substation (MPS)	9					
	53	Tyne 1 2 & 3 Low Voltage Switchgear Assemblies	13					



1. Introduction

This Chapter of the Distribution Substation Plant Manual (DSPM) only contains legacy substation plant related information and drawings showing the standard plant arrangements previously used within Western Power's distribution substations.

2. Disclaimer

The information contained within these drawings shall not be used for anything other than their intended purpose (as stated within this chapter). Other documents that refer to these drawings shall not change the intended purpose whether it is written or inferred.

This Chapter alone does not claim to demonstrate compliance with any Government Regulations or Industry Standards. These drawings are to be read in conjunction with the following Western Power documents:

- i. Western Australian Service and Installation Requirements (WASIR)
- ii. Underground Distribution Schemes Manual (UDSM)
- iii. Distribution Customer Connection Requirements (DCCR)
- iv. Distribution Overhead Line Design Standard (DOLDS) for DSM 3-24 drawing.
- v. Distribution Design Catalogue (DDC)

The drawings within this Chapter are generic in nature and may not be suitable for all substation sites. It is the designer's responsibility to make sure that these drawings are suitable for the proposed substation site prior to use.

3. Compliance with this Chapter of the Manual

This Chapter of the Distribution Substation Plant Manual contains information about legacy plant and the standard to be used for its installation. These drawings can be used as a guide when maintaining existing sites.

This information should not be used for new (green field sites). This information can be used as a reference when existing sites are being upgraded. All new green field and upgraded sites shall meet the current standards in the other Chapters of this manual.

4. Scope

This Chapter will only contain drawings for plant that has been superseded or withdrawn whilst the DSPM is in circulation. All other legacy plant is published within the standard of the day.

These standards include:

- 1. SECWA Distribution Substation Standards Manual 1984 (Black Book) EDM# 23630836
- 2. SECWA Distribution Substation Standards Manual 1993 (White Book) EDM# 23630847
- 3. Western Power DISTRIBUTION SUBSTATION MANUAL (DSM) 1997, 2002 and March 2007:
 - a. INTRODUCTION (EDM# 24016023)
 - b. SECTION 1 CUSTOMER SUPPLY ARRANGEMENTS (EDM# 25675560)
 - c. SECTION 2 HV NETWORK ARRANGEMENTS (EDM# 23580399)
 - d. SECTION 3 SUBSTATION ARRANGEMENTS (EDM# 23581570)
 - e. SECTION 4 KIOSK ARRANGEMENT AND INSTALLATION GUIDE (EDM# 23581608)
 - f. SECTION 5 SUBSTATION FIRE PROTECTION REQUIREMENTS (EDM# 23581631)




- g. SECTION 6 MISCELLANEOUS (EDM# 23935652)
- h. SECTION 7 SUPERSEDED EQUIPMENT INSTALLATION GUIDE (EDM# 23936185)
- i. SECTION 8 DISTRIBUTION AUTOMATION (EDM# 23938100)
- j. SECTION 9 33KV SUBSTATION ARRANGEMENTS (EDM# 23938132)




5. Superseded Equipment Drawings

5.1 Drawing Legend






5.2 Tyree MKI Modular Package Substation (MPS)








	315	22	2375	1463	535	2105	XA2420	Н	U61
	630	6.6/11	2716	1756	855	3110	XA2416	Н	U61
	630	22	2631	1551	715	2695	XA2422	Н	U61
					TYRFF 6/1	1. 22kV -	315 & 630kVA	DISTRIBUTION SUBSTATION PLANT MANUAL	wes 🌓 wes
<u> </u>	1			\bot		1,		DDAWN CC DATE	00 (2010 DRG I



MkI MPS KIOSK GENERAL ARRANGEMENT (NOW OBSOLETE)

DISTRIBUTION SUE PLANT MAN		41	weste	:cubo	wer	
DRAWN: GC	DATE: 08	/2019	DRG. No.			
CHECKED: KG	SCALE:	NTS	DSPM7-01			
APPROVED: AS			REV.	SHT.		
APPROVED: MS					2	







NOTES:

- 1. THE FOLLOWING IS TO BE READ IN CONJUNCTION WITH AS 3798 FOR EARTHWORKS, AS 4678 FOR EARTH RETAINING STRUCTURES AND AS 1597 FOR PRECAST CONCRETE CULVERTS.
- 2. EXCAVATION TO BE DONE IN ACCORDANCE WITH THE CODE OF PRACTICE FOR EXCAVATION.

 A COMPETENT PERSON MUST BE PRESENT AT ALL TIMES DURING THE EXCAVATION, FOUNDATION PREPARATION, INSTALLATION OF CULVERT AND BACK FILL. IF DUE TO SITE CONDITIONS AND CLOSE PROXIMITY TO OTHER STRUCTURES SAFE EXCAVATION CANNOT BE CARRIED OUT THEN TRENCH SHORING SHOULD BE USED.
- 3. LIFTING POINT FOR "TRANSFORMER" TO BE USED FOR TRANSFORMER REPLACEMENT AND TO LIFT COMPLETE ASSEMBLED MPS UNIT. TRANSFORMER MUST LOWERED BE INTO PLACE FROM ABOVE WITHOUT ANY FORCE BEING APPLIED TO THE LV FRAME.
- 4. WHEN LANDING THE MPS TRANSFORMER THE EDGE OF THE CULVERT SHOULD BE LOCATED 30mm FROM THE FRONT EDGE OF MIDDLE CROSS MEMBER WITHIN THE MPS BASE. THIS IS 515mm FROM THE FRONT EDGE OF THE LV FRAME BASE. SEE DETAIL A.
- 5. COMPACTION OF SUBGRADE TO BE A MINIMUM MODIFIED DENSITY RATIO OF 95 % TO AS 1289.6.3.2 FOR A DEPTH OF 1000mm BELOW CULVERT BASE. IN CLEAN SAND THIS MAY BE MEASURED AS 10 BLOWS / 300mm WITH A STANDARD PENETROMETER.
- 6. VOID TO BE FILLED WITH SAND, HAND COMPACTION REQUIRED (NOT BY MACHINE).
- 7. COMPACTED BACKFILL MATERIAL IS TO BE CLEAN SAND. COMPACTION OF THE SAND IS TO BE CARRIED OUT IN LAYERS NOT EXCEEDING 300mm. COMPACTION LEVEL TO ACHIEVE A MINIMUM MODIFIED DENSITY RATIO OF 92 % TO AS 1289.6.3.2. THIS MAY BE MEASURED AS 8 BLOWS / 300mm WITH A STANDARD PENETROMETER
- 8. PRECAST REINFORCED BOX CULVERT AND BASE TO AS 1597 (100kN) STOCK CODE CA0002. NOMINAL (INTERNAL) SIZE OF CULVERT 1244 wide x 914 high x 1220 long. TO BE INSTALLED AS PER AS 1597. EXTERNAL SIZE 1416 X 1022 X 1220
- 9. THE BASE OF THE EXCAVATION IS TO BE A MINIMUM OF 500 mm LARGER THAN THE BASE OF THE CULVERT, ON ALL SIDES. THE SIDES OF THE EXCAVATION ARE TO HAVE A SAFE SLOPE BASED ON SOIL TYPE AND MOISTURE CONTENT.
- 10. IN THE EVENT THAT THE SITE IS HIGHER THAN THE FINISHED LEVELS OF THE NEIGHBOURING AREAS, RETAINING WALLS, ACCESS STEPS AND DAINAGE SHALL BE PROVIDED COMPLYING WITH AS 4678, THE REQUIREMENTS OF THE LOCAL GOVERNMENT AUTHORITY AND WESTERN POWER. THIS WORK SHALL BE CERTIFIED BY A PROFESSIONAL CIVIL ENGINEER (NPER).
- 11. WHERE THERE IS A RISK OF FLOODING OR WHERE GROUND WATER EXISTS, THE SUBSTATION SITE SHALL BE ELEVATED AND RETAINED SO THAT THE CULVERT BASE IS ABOVE THE PREDICTED FLOODING OR HIGHEST POSSIBLE GROUND WATER LEVEL. THE FOUNDATION DESIGN, BACK FILL AND COMPACTION IS TO BE APPROVED BY A QUALIFIED GEOTECHNICAL ENGINEER.
- 12. A COMPACTION CERTIFICATE IN ACCORDANCE WITH as 1289.6.3.2 IS REQUIRED BY WESTERN POWER FOR ALL SUBSTATION INSTALLATIONS.

OBSOLTE (FOR REFERENCE ONLY)

					TITLE				DISTRIBUTION SUB	STATION .	-44 we	eternonwer
					1''''				I PLANT MANII	Δ1	all Mc	grei iihomei
				1	ITVDFF	6/11	221/1	′ – 315 & 630kVA	T EXITT TIXITO			
					111766	. 07 11,	, ZZNV	- YINKU A CIC -	DRAWN GC	DATE 08/2019	9	DRG. No.
					i mki	MPS	KIOSK	INSTALLATION	CHECKED: KG	SCALE: N	ITS	DSPM7-01
					1	C	11101.1	00001 5751	100001150 10			D3F1:17-01
Α	08/2019	NOW OBSOLETE, REFER MKII MPS	KG	MS	1	(iUIII)E	(NUW	OBSOLETE)	APPROVED: AS		RE'	/ SHT
R N	-			APRD	4	00,02	(11011		APPROVED: MS			A 3111 4



5.3 Type 1, 2 & 3 Low Voltage Switchgear Assemblies

